



PRECISION MATTHEWS

HEAVY DUTY FULL SYNTHETIC COOLANT

- Provides excellent lubrication without oil.
- Prevents foaming at high pressure and provides protection against rust and corrosion.
- No effects on machine tool parts, including paint and seals.
- Excellent rejection of foreign contamination, including tramp oils.
- Improved hard water stability, due to the absence of phosphates.
- Biocide package controls bacteria & fungi.
- Non-toxic, Non-irritating, Non-corrosive. Biodegradable and poses no environmental or health risks.

1 Qt/ 946 mL



PRECISION MATTHEWS

HEAVY DUTY FULL SYNTHETIC COOLANT

Heavy Duty Full Synthetic Coolant is a premium quality, water-soluble, oil free, heavy duty synthetic coolant developed for grinding, drilling, cutting, milling, sawing, forming, tapping/threading, knurling, reaming, boring, turning, broaching, shaping/slotting, blanking, stamping of Titanium/Tungsten & Nickel Alloys, Aluminum Alloys, Super Alloys & Stainless Steels, Chromium Alloys, Molybdenum, Carbon & Tool Steels, Cast Irons, Copper Alloys, Powdered Metals, Brass & Bronze, Refractory Metals, Plastics & Composites, Glass and other ceramic materials to provide unique extreme pressure lubrication and part finishes in modern CNC machining operations. It is specially designed with a special corrosion protection package and a biocide package to provide outstanding system protection and minimize the friction and heat between the tools and parts.

Heavy Duty Full Synthetic Coolant is recommended for use in CNC Machining, Gun Drilling, Gang Drills, Lathes, Turning Centers, Tube and Pipe Mills, Sawing & Cut-off, Creep Feed Grinding, Central Systems, Machining Centers, FMS, Roll Forming, Mills, High Speed & High Pressure Machining.

Heavy Duty Full Synthetic Coolant should be diluted with deionized (DI) water to a concentration of 5% to 8% (volume%) depending on the machining operation and type of material.

Note: Always premix coolant before adding to the machine sump. Never add straight water or straight concentrate coolant directly to the machine sump. If mixing by hand, always add concentrate coolant to water, and then agitate. Coolant concentration may be monitored with a refractometer.

WARNING:

Don't pollute. Conserve resources. Return used coolant and container to collection centers.



www.precisionmatthews.com